

Block Dimensions

Stonehedge® 6

General Information

- Absorption...meets or exceeds ASTM c90-75 standards
- Compressive strength...3000 PSI approximate minimum (unless otherwise specified)
- Composition . . . high strength, high density, "0" slump concrete

Unit Information

Stonehedge XL Unit:

6"H X 18" W X 10"D, 64 Lbs. Approx. 0.75 Sq. Ft. Face

Stonehedge XL Colonial Unit:


6"H X 6"/12"W and 18"W X 10"D, 64 Lbs. Approx. 0.75 Sq. Ft. Face

Universal Cap


4"H X 18"W front and 4"H X 14"W back, 54 Lbs. approx.
0.50 Sq. Ft. Front, 0.39 Sq. Ft. Back
Average running length is 16" (see installation manual)

Face Options


- Face patterns Beveled Split Face
- Straight Split Face
- Colonial Split Face




Universal Cap - Front



Stonehedge® 6



Universal Cap - Back




Stonehedge® 6 Colonial

This drawing is furnished for preliminary design purposes only, and should not be used for final design drawings or construction drawings without the certification of a professional engineer registered in the state in which the wall will be constructed

No.	Date.	Revision.	By.

PREPARED BY:



ROCKWOOD
RETAINING WALLS
A better way.

LEGEND

	Impermeable Compacted Fill		3/4" Crushed Stone
	Compacted Fill		Leveling Pad
	Native Soil		Geogrid

Project Name:	XX
Project Location:	YY
Drawing Description:	Block Dimensions

Prepared for:	CCC
Drawn by:	DDD
Checked by:	
Sheet # of \$	
Date:	MM/DD/YYYY
Project Number:	WWWPRO#