

Scout™ Fire Ring Kit

Warm up those cool nights with a Scout Fire Ring kit.



At 42.5" dia. x 16" tall, the Scout Fire Ring fits anywhere. It builds quickly and easily on a paver patio, slab or backyard. Each kit includes four courses of quality Rockwood split-face fire ring block and step-by-step instructions.

OPTIONAL ACCESSORIES:

INSERT - A one-piece heavy-gauge solid steel ring protects block from high heat.

COOKING GRATE - Removable, US Park Service grade steel construction with stay-cool handle and swivel feature.

COVER - Galvanized steel cover keeps children, animals and rainwater out. With or without cooking grate slot.

E-Z ACCESS SPARK SCREEN - Hinged for easy access, this steel screen design helps control flying sparks and ash.

Visit: www.outdoorlivingkits.com




Builds in four easy steps...


Before planning your fire ring project, check with your local zoning commission or HOA for building restrictions and required construction permits. Read and follow step-by-step instructions provided with your fire ring.




Unit availability, color and specifications vary by manufacturer. Contact your nearest Rockwood manufacturer or dealer for more information.




1. Lay base course (16 blocks) on a level, compacted gravel base, paver patio or slab. Fit blocks tightly together.



2. Continue to build, staggering each course. Secure each block to the course below using a small amount of adhesive.



3. Once your fourth course is complete, place and center the solid steel ring insert. Do not use adhesive on insert.



4. To protect block from high heat, fill the interior with a gravel/sand mix to bury all exposed blocks. Let adhesive set for 24 hours before use.

ROCKWOOD
RETAINING WALLS
A better way.™

325 Alliance Place NE
Rochester, MN 55906

phone: (507) 529-2871
fax: (507) 529-2879

www.rockwoodwalls.com



Available at: