

# Super-Stik<sup>TM</sup> Adhesive



Professionals depend on Super-Stik<sup>TM</sup> adhesive for its superior strength, time-tested performance and versatility.

Super-Stik is the ideal solution for Segmental Retaining Walls, Pavers and Masonry. You can even apply it when damp!



Especially formulated for:

- Use on wet or frozen surfaces
- Superior strength and stability
- Works well in extreme temperatures
- Waterproof bond

*Appearance*

*Dependability*

*Efficiency*

**ROCKWOOD<sup>®</sup>**  
RETAINING WALLS

*A better way.<sup>TM</sup>*

# Super-Stik™ MSDS

## Physical Properties (Typical)

Type	Synthetic elastomeric polymer
State	Medium-viscosity mastic
Color	Light tan
Solids	65%
Viscosity	130,000 cps
Calculated VOC (less except solvent):	282 g/L
Weight/gallon	9.0 lbs.
Flashpoint	Less than 0° F.
Freeze/thaw stability	Will not freeze
Storage life	12 months in tightly closed containers at 75° F.

## Application Guidelines

Application temperature	0° to 100° F.
Service temperatures	-20° F. to 120° F.
Method of application	Cartridge/caulking gun

## Coverage (maximum)

Container	Approx. length of bead according to bead diameter:		
	1/8" bead	1/4" bead	3/8" bead
10.5 oz. Cartridge	129 ft.	32 ft.	14 ft.
29 oz. Cartridge	355 ft.	89 ft.	39 ft.

## Caution Statement

**DANGER: EXTREMELY FLAMMABLE.** VAPOR HARMFUL. Contains acetone, hexane, and toluene. Keep away from heat, sparks, and flame. Use only with positive cross ventilation. Avoid breathing vapors. Do not swallow. Do not allow eye contact or prolonged skin contact. Uncured product can cause eye or skin irritation. Prolonged or repeated overexposure to solvents in uncured product can cause central nervous system, peripheral nervous system, eye, skin, liver, kidney or respiratory system effects. **First Aid:** If dizziness or other adverse effects are experienced, move to fresh air; call physician if discomfort persists. If eye contact occurs, flush eyes with water for 15 minutes; contact physician immediately. If swallowed, do not induce vomiting; contact physician immediately. Wash skin contact areas with soap and water; contact physician if irritation persists. For additional information, refer to Material Safety Data Sheet. **KEEP OUT OF THE REACH OF CHILDREN.**

**WARNING:** This product contains toluene, a chemical known to the State of California to cause birth defects or other reproductive harm.

## Working Time

Approx. 20 - 30 minutes for a 1/4" bead

## Working surfaces

Surfaces to be bonded should be clean and free from excessive oil, grease, water, dirt or any other material that may deter adhesion. Apply Super-Stik adhesive to only one of the surfaces to be bonded. NOTE: When bonding subfloors or wet, frozen and treated lumber, nail or screw as recommended by the American Plywood Association.

## Cleanup

Scrape off dried excess with a putty knife. Remove residue with mineral spirits or equivalent solvent. Follow solvent vendor's precautions when using

solvents. NOTE: Test solvent on an out-of-the-way area to make sure it will not mar or attack the surface.

## Product Features

- Extremely versatile-bonds most common building materials
- Exceeds the performance requirements of the American Plywood Association AFG-01 Specification, ASTM D3498 and C557, HUD/FHA Use of Materials Bulletin #60

## Limitations

Super-Stik adhesive is not designed for continuous submersion or for use on polystyrene or polystyrene foams.

**Important Notice:** Our recommendations, if any, for the use of this product are based on tests believed to be reliable. Since the use of this product is beyond the control of the manufacturer, no guarantee or warranty, expressed or implied, is made as to such use or effects incidental to such use, handling or possession or the results to be obtained, whether in accordance with the directions or claimed so to be. The manufacturer expressly disclaims responsibility therefore. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing laws and /or patents covering any material use.

## Ordering Information

Cat. No.	Cartridge Size	Units/Package	Packages/Pallet
56441	10.5 oz.	12	108
56442	29 oz.	12	38



Visit us on the web at:  
[www.super-stik.com](http://www.super-stik.com)

**ROCKWOOD®**  
RETAINING WALLS  
*A better way.™*

325 Alliance Place NE  
Rochester, MN 55906

toll free  
**888.288.4045**  
phone  
**507.529.2871**  
fax  
**507.529.2879**

[www.rockwoodwalls.com](http://www.rockwoodwalls.com)

Available at: